Description

Duct averaging temperature sensors are designed specifically for HVAC system temperature control. The averaging sensors come in thermistor compatible with most BAS systems available today. Averaging sensors come with a foambacked handy box and in 12ft(3.5m), 24ft(7m),39ft(12m) lengths.

Duct averaging temperature sensor should be mounted across a duct in a serpentine fashion with bends in a smooth ark using clip.



12 meter cable with 9 overmolded sensor elements





Clip

Features

- Lengths of 12ft (3.5m),24ft (7m),39ft(12m)
- Five-year warranty
- Cable Property FT4, 105°C, 300V standard or 200°C, 300V high temperature on request.
- Cable Material PVC standard or High temperature silicon available on request.

Specifications


Accuracy		
Thermistor	±0.36°F (0.2°C)	
RTD	±0.5°F (0.28℃)	
Sensor Type		
Thermistor	10 kΩ Type II & III	
RTD	1000Ω	
Temperature Range	-20 °C~80°C	
Stability		
Thermistor/RTD	0.24°F (0.13°C) over five years	
Heat Dissipation	Thermistor,3mW/°C (power needed to raise the temperature by 1°C	
Encolsure Rating	Watertight metalbox,Metal box,Plastic box	
Warranty	5 yeas	

Wire Specifications


SPEC NO	UL2464 20AWG
Reference Standard	UL1581/758
Rated Temperature	80°C
Rated Voltage	300V
Flame Retardant Grade	VW-1
Envronmental Standards	RoHS

Conductor	Sectional Area	AWG/mm	21/0.178±0.008TS
	Conductor Material	/	Tinned Copper Wire
	Sectional Area	mm²	0.52
	Stranded Diameter	mm	0.94
Insulation	Material	1	Pvc
	The Average Thickness	mm	0.28
	Minimum Gauge	mm	0.24
	Insulation Diameter	mm	1.5±0.1
Jacket	Material	/	Pvc
	The Average Thickness	mm	1.05
	Minimum Gauge	mm	0.95
	Overall Diameter	mm	4.8±0.15

Structure Diagram



Part Number Scheme



Wiring Arrangement

